

	Capacities [Contenances]															Lub. grades [Produits]			
	L185		L235		L245		L275		L295		L305		L345		L355SS		L2201	L3001	
	F	DT	F	DT	F	DT	F	DT	F	DT	F	DT	F	DT	DT		F	F	DT
Cooling system [Circuit de refroidissement]	1.36 U.S. gals. 5.3ℓ		1.69 U.S. gals. 6.6ℓ		1.69 U.S. gals. 6.6ℓ		1.69 U.S. gals. 6.6ℓ		1.48 U.S. gals. 5.8ℓ		1.48 U.S. gals. 5.8ℓ		1.79 U.S. gals. 7ℓ		1.79 U.S. gals. 7ℓ	1.69 U.S. gals. 6.6ℓ	1.79 U.S. gals. 7ℓ	Clean water [Eau propre]	
Crank case [Carter moteur]	0.97 U.S. gals. 3.8ℓ		1.56 U.S. gals. 6.1ℓ		1.25 U.S. gals. 4.9ℓ		1.56 U.S. gals. 6.1ℓ		1.56 U.S. gals. 6.1ℓ		1.56 U.S. gals. 6.1ℓ		2.33 U.S. gals. 9.1ℓ		2.33 U.S. gals. 9.1ℓ	1.25 U.S. gals. 4.9ℓ	2.33 U.S. gals. 9.1ℓ	Engine oil CD (DS) [Huile moteur CD (DS)] SAE 30 Above 77°F (25°C) [Plus de 25° C : SAE 30] SAE 20 Between 32°~77°F (0~25°C) [De 0 à 25° C : SAE 20] SAE10W, SAE10W-30 Below 32°F (0°C) [Moins de 0° C : SAE 10W, SAE 10W-30]	
Front axle diff. case [Carter de différentiel AV]	—	0.56 U.S. gals. 2.2ℓ	—	0.59 U.S. gals. 2.3ℓ	—	0.56 U.S. gals. 2.2ℓ	—	0.67 U.S. gals. 2.6ℓ	—	1.02 U.S. gals. 4ℓ	—	1.28 U.S. gals. 5ℓ	—	1.28 U.S. gals. 5ℓ	1.28 U.S. gals. 5ℓ	—	—	1.02 U.S. gals. 4ℓ	Gear oil SAE 80 or 90 [Huile SAE 80 ou 90]
Front axle gear case (right & left) [Carter de réducteur AV (Dr et Gch)]	—	0.20 U.S. gals. 0.8ℓ	—	0.08 U.S. gals. 0.3ℓ	—	0.20 U.S. gals. 0.8ℓ	—	0.08 U.S. gals. 0.3ℓ	—	0.38 U.S. gals. 1.5ℓ	—	0.18 U.S. gals. 0.7ℓ	—	0.18 U.S. gals. 0.7ℓ	0.18 U.S. gals. 0.7ℓ	—	—	0.38 U.S. gals. 1.5ℓ	Gear oil SAE 80 or 90 [Huile SAE 80 ou 90]
Transmission case [Carter de boîte de vitesses]	5.63 U.S. gals. 22ℓ	5.89 U.S. gals. 23ℓ	6.14 U.S. gals. 24ℓ		5.63 U.S. gals. 22ℓ	5.89 U.S. gals. 23ℓ	6.14 U.S. gals. 24ℓ		6.66 U.S. gals. 26ℓ	6.91 U.S. gals. 27ℓ	7.68 U.S. gals. 30ℓ	7.94 U.S. gals. 31ℓ	7.68 U.S. gals. 30ℓ	7.94 U.S. gals. 31ℓ	8.19 U.S. gals. 32ℓ	5.63 U.S. gals. 22ℓ	6.66 U.S. gals. 26ℓ	6.91 U.S. gals. 27ℓ	Multi-grade transmission fluid [Multi-grade transmission fluide] Gear oil SAE 90 (L2201, L3001)
Steering gear box [Boîtier de direction]	0.08 U.S. gals. 0.3ℓ		0.08 U.S. gals. 0.3ℓ		0.08 U.S. gals. 0.3ℓ		0.08 U.S. gals. 0.3ℓ		0.08 U.S. gals. 0.3ℓ		0.08 U.S. gals. 0.3ℓ		0.08 U.S. gals. 0.3ℓ		0.08 U.S. gals. 0.3ℓ	0.08 U.S. gals. 0.3ℓ	0.08 U.S. gals. 0.3ℓ	0.08 U.S. gals. 0.3ℓ	Gear oil SAE 90 [Huile SAE 90]
Power steering oil tank [Réservoir à huile pour la servo-direction]	—		Trace		—		Trace		—		Trace		0.38 U.S. gals. 1.5ℓ		0.38 U.S. gals. 1.5ℓ	—	—	—	SAE 10~20 [SAE 10~20]
Fuel tank [Réservoir de combustible]	5.63 U.S. gals. 22ℓ		7.17 U.S. gals. 28ℓ		5.63 U.S. gals. 22ℓ		7.17 U.S. gals. 28ℓ		8.96 U.S. gals. 35ℓ		8.58 U.S. gals. 33.5ℓ		8.96 U.S. gals. 35ℓ		8.58 U.S. gals. 33.5ℓ	5.63 U.S. gals. 22ℓ	8.96 U.S. gals. 35ℓ	No.2 diesel fuel [Combustible diesel]	
Clutch release hub [Moyeu de débrayage]	Trace (only 2~3 strokes with a hand grease gun) [2 à 3 pressions d'un pistolet de graissage]															SAE multipurpose type grease [Graisse universelle SAE]			
Pedal clutch	[Pédale d'embrayage]										Trace					SAE multipurpose type grease [Graisse universelle SAE]			
Pedal brake	[Pédale de frein]										Trace								
Shaft brake	[Arbre de pédale]										Trace								
Holder top link	[Support de tirant supérieur]										Trace								
Rod lift	[Tirant de relevage]										Trace								
Hub front wheel	[Essieu avant]										Trace (F)								
Pin center	[Lever de transmission aux roues AV]										Trace								
End drag link	[Extrémité de barre de direction]										Trace								
End tie rod	[Extrémité de barre d'accouplement]										Trace (F)								
Cylinder (booster type power steering)	[Cylindre (servo-direction du type servomécanisme)]										Trace								