

Specification table for CAB model

| Model            |                                   |                  | LX2610HSDC   | LX2610HSDCC     | LX3310HSDC                 | LX3310HSDCC                    |
|------------------|-----------------------------------|------------------|--|-----------------|----------------------------|--------------------------------|
| PTO power🌟       |                                   |                  | kW<br>(HP)   | 14.5<br>(19.5)  | 20.1<br>(27.0)             |                                |
| Engine           | Maker                             |                  | KUBOTA   |                 |                            |                                |
|                  | Model                             |                  | D1305-E4-D26Q  |                 | V1505-CR-TE5-D36Q1         |                                |
|                  | Type                              |                  | Indirect Injection. Vertical, water-cooled 4 cycle diesel                |                 |                            |                                |
|                  | Number of cylinders               |                  | 3  |                 | 4                          |                                |
|                  | Bore and stroke                   | mm<br>(in.)      | ϕ78 × 88<br>(ϕ3.1 × 3.5)   |                 | ϕ78 × 78.4<br>(ϕ3.1 × 3.1) |                                |
|                  | Total displacement                | cc<br>(cu. in.)  | 1261<br>(77.0)   |                 | 1498<br>(91.5)             |                                |
|                  | Engine gross power🌟               | kW<br>(HP)       | 18.5<br>(24.8)   |                 | 23.0<br>(30.8)             |                                |
|                  | Rated revolution                  | rpm              | 2500   |                 |                            |                                |
|                  | Low idling revolution             | rpm              | 1100   |                 | 1300                       |                                |
|                  | Maximum torque                    | N·m<br>(ft·lb)   | 84.0<br>(62.0)   |                 | 105.4<br>(77.7)            |                                |
|                  | Battery                           |                  | 12 V, RC : 80 min, CCA : 430 A   |                 |                            | 12 V, RC : 90 min, CCA : 480 A |
| Capacities       | Fuel tank                         | L<br>(U.S.gals.) | 32<br>(8.4)  |                 |                            |                                |
|                  | Engine crankcase<br>(with filter) | L<br>(U.S.gals.) | 4.0<br>(4.2)   |                 | 4.7<br>(5.0)               |                                |
|                  | Engine coolant                    | L<br>(U.S.gals.) | 4.3<br>(4.5)   |                 |                            |                                |
|                  | Transmission case                 | L<br>(U.S.gals.) | 15<br>(4.0)  |                 |                            |                                |
| Dimensions       | Overall length<br>(without 3P)    |                  | mm<br>(in.)  | 2640<br>(103.9) |                            |                                |
|                  | Overall width (min. tread)        |                  | mm<br>(in.)  | 1365<br>(53.7)  |                            |                                |
|                  | Overall height                    |                  | mm<br>(in.)  | 2150<br>(84.6)  |                            |                                |
|                  | Wheel base                        |                  | mm<br>(in.)  | 1666<br>(65.6)  |                            |                                |
|                  | Minimum ground clearance          |                  | mm<br>(in.)  | 370<br>(14.6)   |                            |                                |
|                  | Tread                             | Front            | mm<br>(in.)  | 935<br>(36.8)   |                            |                                |
|                  |                                   | Rear             | mm<br>(in.)  | 1050<br>(41.3)  |                            |                                |
| Weight           |                                   |                  | kg<br>(lbs.)   | 1040<br>(2293)  | 1160<br>(2557)             |                                |
| Clutch           |                                   |                  | Not applicable   |                 |                            |                                |
| Traveling system | Tires                             | Front            | 7-12   |                 |                            |                                |
|                  |                                   | Rear             | 12.4-16  |                 |                            |                                |
|                  | Steering                          |                  | Hydrostatic type power steering  |                 |                            |                                |
|                  | Transmission                      |                  | Main-hydrostatic transmission, 3 range gear shift (3 forward, 3 reverse) |                 |                            |                                |
|                  | Brake                             |                  | Wet disk type  |                 |                            |                                |



|                | Model                               |                          | LX2610HSDC                                  | LX2610HSDCC            | LX3310HSDC | LX3310HSDCC |
|----------------|-------------------------------------|--------------------------|---|------------------------|------------|-------------|
|                | Minimum turning radius (with brake) | m<br>(feet)              | 2.1<br>(6.9)                                |                        |            |             |
| Hydraulic unit | Hydraulic control system            |                          | Position control                            |                        |            |             |
|                | Pump capacity                       |                          | L / min<br>(gals / min)                     | 33.1<br>(8.7)          |            |             |
|                | 3-point hitch                       |                          | SAE Category 1                              |                        |            |             |
|                | Max. lift force                     | At lift points           | kg<br>(lbs.)                                | 970<br>(2139)          |            |             |
|                |                                     | 24 in. behind lift point | kg<br>(lbs.)                                | 760<br>(1676)          |            |             |
| PTO            | Rear-PTO                            |                          | SAE 1-3/8, 6 splines                        |                        |            |             |
|                | PTO / Engine speed                  |                          | rpm   | 1 speed<br>540 / 2398  |            |             |
|                | Mid-PTO                             |                          | USA No. 5 (KUBOTA 10-tooth) involute spline |                        |            |             |
|                | PTO / Engine speed                  |                          | rpm   | 1 speed<br>2500 / 2500 |            |             |

The company reserves the right to change the specifications without notice.

